


ART SELECT

TECHNICAL DATA



	Standard	Result
Thickness	3mm	
Wear layer	0.7mm	
Guarantee	Handcrafted Wood, Oak Royale, Oak Premier and Parquet Commercial Heavy Duty 15 years* Domestic Heavy Duty 20 years* Glass: Commercial Heavy Duty 10 years Domestic Heavy Duty 15 years*	
Bevelled edge	Yes (except Glass)	
Standards	EN 649 ASTM F-1700	
Classification	Commercial Heavy Duty use Domestic Extra Heavy Duty use	
Reaction to fire	AS 9239.1: 2003	CRF: Hand Crafted Wood 9.6 kW/m ² Oak Royale 10.5 kW/m ² Glass 10.8 kW/m ² Oak Premier 8.5kW/m ² Parquet 8.5kW/m ² Smoke Value: Hand Crafted Wood 151% min. Oak Royale 48% min. Glass 137% min. Oak Premier 177% min Parquet 220% min
Slip resistance	AS/NZS 4586: 2004	
Staining resistance	EN 423 ASTM F-925	Class 0 Pass
Light fastness	ISO 105-B06 ASTM F-1515	≤ 6 < 8
Abrasion resistance	EN 660-2 ASTM 3884	Group T Pass
Dimensional stability	EN 434 ASTM F-2199	≤ 0.25% Pass
Acoustic impact noise reduction	EN ISO 140-8 EN ISO 717-2	ΔL _m = 2dB ¹
Electrical behaviour body voltage	EN 1815	Pass
Indentation - residual	EN 433 ASTM F-1914	≤ 0.1mm < 8%
Castor chair continuous use	EN 425	Pass
Thermal conductivity	ISO 8302	0.0147kW/m ²
Adhesive	General use: Karndean Mega-Bond High temperature: Karndean 8000 2-part Polyurethane	
Recycling	Suitable	

		Slip Resistance	
Product Code	Size (mm)	Oil-Wet Ramp	Wet Pendulum
EW01, EW02, EW03	915 x 152	R10	Z
EW01, EW02, EW03	915 x 152		
AP01, AP02, AP03	228 x 76	R9	Y
HC01, HC02, HC03 HC04, HC05, HC06	915 x 152		
RL01, RL02, RL03, RL04	1219 x 178		

For full test results please contact Karndean International.

* Subject to terms
¹ Result is Ln,w + C¹ = 57dB when installed on Regupol 4515 acoustic underlay

Manufactured to:

FOR MORE INFORMATION :

Australia	New Zealand
Freecall: 1800 810 920	Freecall: 0800 442 101
Email: enquiries@karndean.com.au	Email: info@karndean.co.nz
Website: www.karndean.com.au	Visit: www.karndean.co.nz

